FRENIC-Eco Series Inverters for Fan and Pump Applications

Takashi Nakanishi Yasushi Kondo Osamu Mizuno

1. Introduction

Reflecting the growing awareness of global environmental conservation throughout the world in recent years, and as represented by the enforcement of Kyoto Protocol, there is a demand for energy savings and conservation in order to reduce CO_2 emissions that cause global warming. In fan and pump applications in heating, ventilation and air-conditioning systems (HVAC) and the like, substantial energy savings have been realized through the use of inverters. In such applications, the use of inverters is already widespread, and marketplace requirements for improved functionality and higher performance have recently increased.

In response to those requirements, newly developed FRENIC-Eco series was specifically designed for fan and pump applications, and realizes improved ease-of-use with the most suitable functions, performance and options for use with fans and pump, as well as compact size and low cost by optimized design using semiconductor devices in the main circuit. Moreover, since FRENIC-Eco series is environmentally friendly and complies with standards for example designed for long-service life and low noise, and conforming to EU's RoHS directive^{*1}, it is positioned as global product that can be used throughout the world.

This paper describes the features of FRENIC-Eco series.

2. Abundant Model Varieties

Figure 1 shows the appearance of FRENIC-Eco series, and Table 1 lists its model varieties.

To provide wide range of capacities for use in applications ranging from home-use pumps to ventilation systems in tunnels, 3-phase 200 V series from 0.75 to 75 kW and 3-phase 400 V series from 0.75 to 220 kW were developed as standard models. In addition to these standard models, a series with built-in DC reactor for suppressing harmonics in power supply, a

Fig.1 Appearance of FRENIC-Eco series



Table 1 Variety of FRENIC-Eco series models

Item	Varieties		
Standard Type	3-phase $200 V$	$0.75 \mbox{ to } 75 \mbox{ kW} \ (90 \mbox{ to } 110 \mbox{ kW})$	
	3-phase $400 V$	0.75 to 220 kW (280 to 500 kW)	
DC reactor (DCR) built-in type	3-phase $200 V$	0.75 to 75 kW	
	3-phase $400 V$	0.75 to 75 kW	
EMC filter	3-phase 200 V	0.75 to 15 kW	
built-in type	3-phase $400 V$	0.75 to 15 kW	
Waterproof type	3-phase $200 V$	0.75 to 45 kW	
(IP54 enclosure)	3-phase $400 V$	0.75 to 90 kW	

) are intended to be lineup in series.

series with built-in electromagnetic compatibility (EMC) filter for reducing electromagnetic noise, and a waterproof (IP54) series for use in wet environments (such as pump applications) have also been developed as semi-standard models.

To simplify maintenance, Fuji Electric has also developed inverter support loader software that enables function code setting, operation monitor, test run, and the like on PC.

To improve ease of use, optional interface cards such as LONWORKS^{*2}, DeviceNet^{*3}, RS-485, and relay output as well as, optional multi-function keypad

^{*1:} RoHS directive is restriction on the use of certain hazardous substances in electric and electronic devices.

having built-in copying function with improved operation and display capabilities, and external cooling attachment moving rear heat source to outside the control panel to reduce panel size have been developed.

3. Environmental Design

3.1 Energy-savings operation function

Previous energy-savings operation function used a control method that minimized motor loss in accordance with load condition. Newly developed FRENIC-Eco series, however, utilizes a new control method that minimizes both amount of electric power consumed by the inverter itself (inverter loss) and the motor loss. Figure 2 compares characteristics of "inverter + motor" efficiency vs. motor output when using previous method, new method of energy-savings operation, and no energy-savings operation. New method is capable of achieving energy savings in several percent greater than that in previous method.

3.2 RoHS compliance

Even though general-purpose inverters are presently excluded from the EU's RoHS directive, FRENIC-Eco series is steadily advancing toward conformance with RoHS directive in consideration of growing environmental awareness in the marketplace.

3.3 Noise reduction including peripheral devices

By insulated gate bipolar transistor (IGBT) switching in main circuit and field-effect transistor (FET) switching in control power supply, inverter generates conducted noise that travels through stray capacitance with respect to ground and radiated noise that travels as electromagnetic waves, and these may cause incorrect operation in other peripheral devices. FRENIC-

- *2: LONWORKS is a registered trademark of Echelon Corp. in the US and other countries.
- *3: DeviceNet is a registered trademark of the Open DeviceNet Vender Association (ODVA).



Fig.2 Efficiency with and without energy-savings operation function

Eco series implements the following measures to reduce noise generation.

- (1) Reducing voltage fluctuation (dv/dt) of main circuit's IGBT
- (2) Use of a structure that cuts off noise conduction path of control power supply FET
- (3) Use of a structure that reinforces chassis ground shield

Additionally, the product line has been expanded to include semi-standard series having built-in EMC filter, which conforms to EU's EMC standard (EN61800-3).

3.4 DC reactor built-in type

FRENIC-Eco models with built-in DC reactor (0.75 to 75 kW) are added as to semi-standard series. Since models of motor ratings 22 kW and below also contain built-in zero-phase reactor and capacitive filter, they conform to 2004 version of "Public Building and Construction Standards" issued by Japan's Ministry of Land, Infrastructure and Transport. Models of motor ratings 30 kW and above can conform to that standard by adding zero-phase reactor.

3.5 Easier maintenance

In order to reduce maintenance labor involved in replacing parts of already installed equipment, all limited life parts used in inverter are designed to have an optimal layout (heat countermeasure) and selected from long life parts, to achieve longer design service life. Table 2 lists design service life of various parts in case of 40°C inverter ambient temperature and 80 % load condition of inverter rated current.

Moreover, by storing and displaying following maintenance information to keypad or by sending it to upper-level system, enhance of equipment reliability and simple maintenance can be performed.

- \circ capacitance of main circuit
- cumulative operating time of electrolytic capacitors on printed circuit board
- $\circ~$ cumulative operating time of cooling fan
- cumulative operating time of inverter
- cumulative operating time of motor
- \circ number of times started

3.6 Easy replacement of cooling fan

As cooling fan used in FRENIC-Eco has long life, it

Table 2 Design service life of aging parts

Part name		Design service life	
Main circuit capacitor		10 years	
Electrolytic capacitor on the printed circuit board		10 years	
Caaling fam	30 kW or below	10 years	
Cooling ian	37 kW or above	7 years	

Load condition : 80 % of output rated current Ambient temperature : 40°C has low likelihood of requiring replacement. Moreover, its structure allows easy replacement in the case of failure.

7.5 to 30 kW models can be replaced with simple one-touch operation, and 37 kW and larger models can be replaced from the front panel of the inverter, without removing inverter from control panel. Figure 3 shows cooling fan replacement procedure.

4. Optimal Functions for HVAC

4.1 Current output of analog monitor

Previously, information such as output frequency or output current was 0 to 10 V analog voltage output signal. With newly developed FRENIC-Eco series, such information can also be output as a 4 to 20 mA current signal, which is commonly used as instrumentation signal. Therefore, even in cases where control line wires are long and 4 to 20 mA is required, there is no need for an external device such as a voltagecurrent converter.

4.2 PID control function

In fan and pump applications, tasks such as control of temperature, flow rate, and pressure are performed by proportional, integral, derivative (PID) function of inverter or by an external PID regulator. Since newly developed FRENIC-Eco series is equipped with enhanced PID control function that supports multiple mode of manual speed commands, alarm output function, low water-flow stop function, and an anti-reset windup function that prevents PID control overshoot, it is suitable for various fan and pump applications. Figure 4 shows a block diagram of PID control function.

4.3 Commercial switching sequence

For fan and pump applications, inverter often operates on commercial power supply mode at or near the commercial frequency, and drives in cases where its frequency is required less than commercial frequency, to improve efficiency. Moreover, in cases where it is not possible to stop equipment that is using inverter, operation may be continued by changing over to

Fig.3 Replacement of cooling fan (7.5 to 15 kW)



commercial operation when inverter issues an alarm stop or fails.

In these cases, the changeover between commercial and inverter operation was traditionally implemented by external sequence control circuit outside the inverter. Since FRENIC5000G11S/P11S series housed a portion of that external circuitry inside the inverter, it simplifies external sequence circuit. As FRENIC-Eco series additionally provides automatic changeover internal sequence to commercial operation in response to an alarm stop initiated by inverter protection function, it enables further simplification of external circuitry.

4.4 Pick-up function

FRENIC-Eco series is equipped with pick-up function that uses high-speed current control function same as in FRENIC-Mini series. With this function, even when idling fan, turning by natural convection or the like, is started by inverter, smooth pick-up is possible regardless of motor's direction of rotation.

Figure 5 shows characteristics of idling motor started by pick-up function.

4.5 Power monitor function

Monitoring information of amount power consumption (kW), cumulative power consumption (kWh) and cumulative power rates (price in local currency per





Fig.5 Characteristics of a motor started by the pick-up function



kWh) is displayed on keypad, or is transmitted to an upper-level system to enable power monitoring of whole system consisting of other devices such as inverters.

4.6 Analog input monitor function

By analog input monitor function provided in FRENIC-Eco series, where signals such as flow rate or temperature in air conditioning equipment are connected to the inverter's analog input pins, and conversion factors to convert those signals into physical values such as temperature and pressure are preset, those values can be displayed synthetically on the inverter's keypad or transmitted to an upper-level system, without requiring the use of dedicated flow meters or pressure gages.

5. Options

5.1 Multi-function keypad

FRENIC-Eco series is provided with a keypad as standard equipment, and this keypad provides the capability for remote operation. As an option, multifunction keypad featuring a backlight liquid crystal display (LCD) and large 5-digit 7-segment light-emitting diode (LED) display is also available. Figure 6 shows the appearance of this multi-function keypad. Special features of multi-function keypad are listed below.

- (1) Can be attached to inverter unit instead of standard keypad (allows remote operation via a LAN cable)
- (2) A "REM/LOC" switch key makes it possible to switch between remote operation via external operation commands, or local operation with inverter unit
- (3) Can store and read out function codes for up to 3 inverters
- (4) Communication debug function enables testing and verification of transmission data

Fig.6 Appearance of multi-function keypad



(5) Capable of information display up to the last 4 generated alarms, and capable of setting and verifying function code data

5.2 Network options

To communicate with upper-level controller, Fuji Electric provides interface cards that support LONWORKS and DeviceNet. Since LONWORKS is well suited for building networks, it realizes flexible system

Table 3 F	Functions	of inverter	support	loader	software
-----------	-----------	-------------	---------	--------	----------

Name of function	Description
Function code setting	Reading, editing and comparison of function code data, term searches, user settings, etc.
Operation monitor	I/O monitor, system monitor, alarm monitor, meter display
Multi- monitor	Simultaneous monitoring of two or more inverters
Test run	 Run/stop and frequency setting can be entered at the loader for starting test run. Monitoring of the operation status (such as the output frequency)
Real-time trace	Arbitrary data can be monitored in real time.
Other	Communications setting, connection setting

Fig.7 Function code setting screen

10 ISAN BORD	Change Function table No.	Function code name	Setting value Range of setting	Factory setting value Data cannot strange to open	
E Code group	F00	Data protection	E-5 to 1	Ð	Enable
Fcode	#01	Frequency command 1	1 Voltag av 010 7	1	Desable
- Loate	102	Operation method	d : REVPAD operation 6.12 or Down	h Kendo	Disable
Coode	F00	Maximum formers in	1 : Voltage input l'Terminal 121 (0.5	0+10V DCx	Disable
Poste	FOA	Roos hansonly	2 : Current input (Terminal C1) (4.t	p 38mA DC)	Disable
Hicode	105	Rated withose (a) have been	and 2 Votage input (Terminal 12) and	Corrent input (Terminal C1)	Disable
woode	F07	Acceleration time 1	 Voltage input (Terminal V2) (Dit 	0+10V DC)	Englie
conde	F00	Darakeation time t	TO PROVE CONTRA	70.0	Enable
Charge Facher	100	Tatasa koosi	74 50 1 20 0 1	20.0	Eastia
- Cantents of chara	510	Elastance Barriel Colectile	a root 0.5 km 7		Eastie
It Use definition	F10	Electronic mention (Order) in	1122 0.02 to 2000 s	27.62	Easter
- Uper defention		ENLISTIC PRIMA (OVERLas	11.35 COLD 2100A	22.30	Litette
Use definition	*12	Electroner mermal (i nerma	I save block config-and set that tools		3
Uper definition	+14	Hestat mode atter moment			
E Cade for conveur	715	Prequency Initial (Pleaso			
S code	¥16	F SHELMISCY EFTERM (HORDETO	Estabilishment range: 0 to 7		
-PI COOR	+18	East date (1)	1 - Multivery install Transmission 721 (1) to a 10		
W 0000	+20	DC trave (starting requenc	the [1: Vontage input [Terminal 12] (Units * 199 UC) 2: Current Pup (Terminal 12] 410 20mA DC) 3: What is the formation of the second second second second control to the second control of the second control 5: Voltage input [Terminal 12] (bit is * 10V DC) 7: UP DOWN control		
-7 code	721	OC trake (Braking level)			
	+22	DC brake (Braking time)			
THE .	F23	Stating fraquency			
	#25	Stop frequency			
- Completion recall	F26	Mator sound (Carrier Reque			
- Search result	¥27	Mator sound (Sound tone)			
	729	FMA terminal (Select)			
	F30	FMA terminal (Output gain)			
	£31	EMA terminal (Monitor object			
	\$23	FMP terminal (Pulse rate)			



Select monitor item	Frequency command Hz		Assign an input signal	Noma
Output frequency (before slip)	60.00 Apply	X1	[3-wire operation stop command [HLD]	Oper
		7/2	Coast-to-stop command (BX)	Ope
0.0.0.0.00000	Select monitor item	×3	Alam reset [RST]	Oper
Operation status Hz	Frequency command 💌 60.00Ha	>:4	Freq.set2/Freq.set1 [Hz2/Hz1]	Ope
EW/D	Motor speed I 800r/min	>\5	Remote/local [LOC]	Oper
FVVD	Output voltage • 380.0V	>6		
	Switch of Freq. command, Ope. command	×7		
STOP FWD	3 : Freq. = Loader. Ope. = Loader 💌	1 30	-	
DECET DEV	Apply	FWD	Forward operation command [FWD]	Ope
RESET REV		REV	Reverse operation command [REV]	Ope
	Update inverter information Reliezh			

for building's internal control such as air conditioning. In the future, Fuji Electric intends to provide interface cards that support various other networks such as PROFIBUS-DP^{*4} and CC-Link^{*5}.

5.3 Inverter support loader software

Inverter support loader software that runs on Windows^{*6} is available to support function code setting, operation monitoring, test runs and the like.

Table 3 lists function of the inverter support loader software, Fig. 7 shows an example screenshot of function code setting, and Fig. 8 shows an example screenshot of test run.

6. Main Circuit Technology

FRENIC-Eco series uses suitable main circuit semiconductor devices matched to variable torque characteristic of fan and pump applications.

Moreover, smaller size and lower cost are realized

*6: Windows is a registered trademark of Microsoft Corp. in the US and other countries.

through the use of newly developed low-thermal resistance metal circuit board (7.5 to 15 kW), where ceramic circuit board was used internally in the past, and the use of power module that integrates the converter unit and inverter unit previously separated.

Additionally, electromagnetic analysis and simulation techniques were used to design internal bus bar that connects main circuit's IGBT and capacitor. Since as a result, shape of the internal bus bar and layout of IGBT device and the main circuit's capacitor are optimized, it enables inductance reduction of the internal wiring and a uniform distribution of current, and realization of more compact size and lower cost for snubber circuit and main circuit's capacitor.

7. Conclusion

Features of FRENIC-Eco series inverter for fan and pump (variable torque load) applications have been described above. These inverter models feature enhanced functions and performance for fan and pump applications in order to achieve significant energy savings, and are specifically-designed products that will develop further use of inverters. Looking ahead to future trends of fan and pump market, Fuji Electric intends to continue to create products that satisfy the needs of the marketplace.

^{*4:} PROFIBUS-DP is a registered trademark of the PROFI-BUS User Organization.

^{*5:} CC-Link is a registered trademark of the CC-Link Association.



* All brand names and product names in this journal might be trademarks or registered trademarks of their respective companies.